

IP-FXS2

Specifications	
Network Protocol	<p>SIP v1 (RFC2543), v2(RFC3261)</p> <ul style="list-style-type: none"> -Outbound proxy -Support backup proxy registration -Support IP or domain name for primary and secondary proxy address and auto switching is enabled <p>IP/ICMP/ARP/RARP/SNTP TFT Client /DHCP Client/PPPoE Client Telnet/HTTP Server DNS Client</p> <p>NAT Traversal</p> <ul style="list-style-type: none"> -STUN -UPnP <p>Support ToS Security</p> <ul style="list-style-type: none"> -HTTP 1.1 basic/digest authentication for Web Setup -MD5 for SIP authentication (RFC2069/RFC2617)
Voice Feature	<p>Voice Codec</p> <ul style="list-style-type: none"> -G.711: 64k bit/s (PCM) -G.723: 1:6.3,/5.3, bit/s -G.726: 16k/24k/32k/40k bit/s (ADPCM) -G.729A: 8k bit/s (CS-ACELP) -G.729B: adds VAD & CNG to G.729 <p>VAD: Voice Activity Detection CNG: Comfortable Noise Generator LEC: Line Echo Canceller Packet Loss Compensation</p> <p>DTMF</p> <ul style="list-style-type: none"> -In-Band DTMF -Out-Band DTMF -SIP Info <p>Tone Generation</p> <ul style="list-style-type: none"> -Ring Tone -Ring Back Tone -Dial Tone -Busy Tone -Programming Tone
Call Function	<p>Call Hold Call Waiting Call Forwarding Caller ID Flash Volume Adjustment Speed Dial Key Phone Book</p>
Firmware and Configuration Update	<p>Web Browser Telnet Voice Configuration TFTP HTTP</p>
Weight:	0.44lbs (0.2kgs)
Dimensions:	4" x 4" x 1.4" (165mm x29mm x 139mm)



Mechanical Specifications	
Network Interface:	RJ-45 A. LAN X1 for connecting to HUB or ATU-R directly B. PC X1 for PC Connection
FXS Interface:	RJ-45 A. LAN X 1 for connecting to HUB or ATU-R directly B. PC X 1 for PC Connection RJ-11 A. Phone X1
Environment	AC Power: 110-220 +/- 10V 60Hz +/- 3Hz Temperature: 0°C - 40°C (32°F - 104°F) Humidity: 10% - 90% RH
Weight:	0.44 lbs (0.2kgs)
Dimensions:	4" x 4" x 1.4" (165mm x 29mm x 139mm)

Centro de Servicio

Index Datacom, S.A. de C.V.

Garantía

12 Meses a través de RMA

Términos

Precios en USA Dólares Contado Riguroso
Sujeto a disponibilidad.

